



**Specifications Ledvance LED
Downlight Performance DN155 14W
1600lm 65D - 840 Cool White | 180mm
- IP54 - Dali Dimmable**

[View Product](#)

General Information

| | |
|--------------------------|------------------------------------|
| SKU | 238967 |
| EAN | 4058075459311 |
| Brand | Ledvance |
| Manufacturer Name | DL UGR19 DN155 PFM 14W/840 DALI WT |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 70000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable |
| Colour Code | 840 Cool White |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Driver Included | Yes |
| Beam Angle (degree) | 65 |

| | |
|--------------------------|--------------------------------|
| Luminous Efficacy (lm/W) | 115 |
| Power factor | >0.90 |
| Installation Depth (mm) | 100 |
| Unified Glare Rating | < 19 - for offices and schools |
| Optical Cover | PC (Polycarbonate) |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|------------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 155 |
| IP-rating | IP54 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature | -20 to +45 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Fixture Connection | Screw terminal, 5-pole |
| Series | DN155 |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 65 |
| Diameter (mm) | 180 |

Why Any-lamp?

Sensor Information

 Order from the **largest lighting specialist** in Europe  **Customised** quotation
 Type of sensor No Sensor

 Up to **7 years warranty**  **Easy** return process